



Seagull Safety

20J-F6 SAFE AREA

Detector Head / Junction Box Assembly



Specification Sheet Ref C993

SENSOR	Type – F6
Classification	Certified flameproof IECEX/ATEX Exd IIC T6 Gb Extb IIIC T85°C D6
Certificates	SIRA 08ATEX 1313X IECEX SIR08.0123X
Material	Stainless Steel 316 S16
Ingress Protection	IP63 + weathershield IP64
Data sheet	C994
Mounting Thread	20mm 1.5mm Pitch – options 25mm, $\frac{3}{4}$ NPT
Accessory Mount	Fixing thread 33.3mm 1.25 pitch



JUNCTION BOX	Type – 20J
Ingress Protection	IP65
Material	Polycarbonate
Finish	Light Grey RAL 7035
Entries	Not Specified – top, bottom, sides, rear
Termination	3 wire terminal or flammable CV transmitter (C323)
Weight	265gms
Dimensions	122mm x 120mm x 56mm
Mounting	4 – Internal fixing points @ 90mm x 110mm

ACCESSORIES

Universal Fitting (weather cone/test gas fitting)	003-060
Collector Cone + Universal Fitting	003-062
Flow Block	003-063

SEAGULL SAFETY LTD
45 Chestnut Avenue, Wokingham RG41 3HW
Berkshire, England
Tel: (44) 118 978 5986
Fax: (44) 118 977 5261
info@seagullssafety.com

SEAGULL SAFETY (SINGAPORE) PTE LTD
1 Genting Link, #07-06, Perfect Industrial Building
Singapore 349518
Tel: (65) 6747 9646
Fax: (65) 6744 4028
info@seagullssafety.com

