



DESCRIPTION

THE Ex15VT IS AN EXPLOSIONPROOF ELECTRONIC SOUNDER WITH A CHOICE OF UP TO 64 TONES (50 STANDARD AND 14 CUSTOMISED) AND UP TO FOUR 8 SECOND VOICE MESSAGES. THE UNIT MAY BE CONFIGURED TO GIVE UP TO FOUR STAGES OF ALARM WITH ALL STAGES FULLY CUSTOMER PROGRAMMABLE. GIVING ANY COMBINATION OF TONE, VOICE/SOUND OR TONE + VOICE ALL OUTPUTS ARE SYNCHRONISED ON MULTI-SOUNDER SYSTEMS.

MODEL :
VOICETONE Ex15VT

SPECIFICATION :

- VOLTAGE : 16-36VDC(TONE ONLY : 12-36VDC)
- CURRENT : 400mA@24VDC (1000Hz)
- N.B. A RANGE OF VOLTAGE CONVERTERS IS AVAILABLE FOR MAINS POWERED SYSTEMS
- AUDIBILITY : 107dB-118dB SPL (3dB VOLUME CONTROL)
- ALARM TONES : SEE DRWG. NO. SS66100-68-001
- RATING : CONTINUOUS
- OPERATING TEMP : -25°C TO +55°C
- MATERIAL : INJECTION MOULDED ALUMINIUM DS 4261 EQUAL TO LM6 STAINLESS STEEL BRACKETS & FITTINGS
- WEIGHT : 3 KG
- FINISH : ALUMINIUM - HARD ANODISED PAINT - POLYESTER FIRE RED(RAL 3000)
- CABLE ENTRY : 1 OR 2 x 20mm
- INGRESS PROTECTION : IP 67
- TERMINALS : 7 x 2.5mm²
- CERTIFICATION : 1. NEMKO 98ATEX104
Ex II 2G
 EExd IIB+H₂ T6
 2. NEMKO Ex91Y263
 Exds IIB+H₂ T6
- APPROVED ZONES : ZONE 1 & ZONE 2

ALL DIMENSIONS ARE IN MM

REV.	DATE	DESCRIPTION	DRAWN	CHK'D
0	15.08.01	ISSUED FOR APPROVAL	S.A	



HEAD OFFICE :

SEAGULL SAFETY LTD

45 CHESTNUT AVENUE
WOKINGHAM, BERKSHIRE
RG41 3HW, ENGLAND UNITED KINGDOM
Tel:44-118-978 3978 Fax:44-118-977 5261

REGIONAL OFFICE :

SEAGULL SAFETY (S) PTE LTD

1 GENTING LINK
#07-06 PERFECT INDUSTRIAL BUILDING
SINGAPORE 349518
Tel: (65) 747 9646 Fax: (65) 744 4028

TITLE :

**Ex15VT VOICETONE
EXPLOSIONPROOF SOUNDER**

DRAWN BY	YAP	DATE	15.08.2001
CHECKED BY	ANDREW	DATE	

DRWG NO :	SS66100-64-201	REVISION	0
-----------	----------------	----------	---

THIS IS THE PROPERTY OF SEAGULL SAFETY LTD AND IS ONLY ISSUED ON CONDITION THAT NO COPY IS TAKEN OR REPRODUCTION OR DISCLOSURE TO A THIRD PARTY EITHER WHOLLY OR IN PART IS MADE WITHOUT THE WRITTEN CONSENT OF SEAGULL SAFETY LTD.