



DESCRIPTION

FLAMEPROOF & WEATHERPROOF MOTOR DRIVEN SIREN

MODEL

FP10

FLAMEPROOF CERTIFICATION

- ATEX APPROVED FOR ZONE 1 & ZONE 2 USE
- Ex II 2 G EEx d IIC T4 EEx de IIC T4

CONSTRUCTION

CAST ALUMINIUM

SPECIFICATION

- MOUNTING : HORIZONTAL MOUNT
- SOUND OUTPUT @ 1 METRE : 140 dB
- SOUND FREQUENCY : 475 Hz
- VOLTAGE : 400 VAC
- PHASE : 3
- MOTOR POWER : 5500 WATTS
- NORMAL RATING : CONTINUOUS
- START CURRENT : 55 Amps (400 V)
- RUN CURRENT : 11 Amps (400 V)
- WEIGHT : 80 kg
- INGRESS PROTECTION : IP55
- FINISH : ENAMEL GREY, RED ROTOR
- OPERATING TEMP. : -20°C TO +40°C

HEAD OFFICE :

SEAGULL SAFETY LTD
 45 CHESTNUT AVENUE
 WOKINGHAM, BERKSHIRE
 RG41 3HW, ENGLAND UNITED KINGDOM
 Tel: 44-118-978 3978 Fax: 44-118-977 5261

REGIONAL OFFICE :

SEAGULL SAFETY (S) PTE LTD
 1 GENTING LINK
 #07-06 PERFECT INDUSTRIAL BUILDING
 SINGAPORE 349518
 Tel: (65) 6-747 9646 Fax: (65) 6-744 4028

TITLE :

**FP10 FLAMEPROOF MOTOR
 DRIVEN SIREN**

DRAWN BY SA DATE: 07.12.2002

CHECKED BY AD DATE: 09.12.2002

DWG NO.:

SS77100-112

REVISION
 0



THIS IS THE PROPERTY OF SEAGULL SAFETY LTD AND IS ONLY ISSUED ON CONDITION THAT NO COPY IS TAKEN OR REPRODUCTION OR DISCLOSURE TO A THIRD PARTY EITHER WHOLLY OR IN PART IS MADE WITHOUT THE WRITTEN CONSENT OF SEAGULL SAFETY LTD.

| REV | DATE | ISSUED FOR APPROVAL | DESCRIPTION | DRAWN | CHECK'D |
|-----|----------|---------------------|-------------|-------|---------|
| 0 | 07.12.02 | S.A. | | A.D. | |