



DESCRIPTION
 FLAMEPROOF & WEATHERPROOF
 MOTOR DRIVEN SIREN (SINGLE ROTOR)

MODEL
 FP6

BASEEFA CERTIFICATION
 EExd IIB T6

SPECIFICATION
MOUNTING
 : HORIZONTAL MOUNT

SOUND OUTPUT @ 1M
 : 135dB

SOUND FREQUENCY
 : 470 Hz

VOLTAGE
 : 400VAC 3 PHASE

MOTOR POWER
 : 2.2KW

NORMAL RATING
 : 15 MIN

START CURRENT
 : 33A (400V)

RUN CURRENT
 : 4.5A (400V)

OPERATING TEMP
 : -20°C TO +40°C

INGRESS PROTECTION
 : IP55

WEIGHT
 : 91Kg

FINISH
 : ENAMEL GREY, RED ROTOR

REV	DATE	DESCRIPTION	DRAWN	CHKD
1	24/07/93	REVISED TBK	SA	
0	19/07/93	ISSUED FOR APPROVAL	SA	



HEAD OFFICE :
SEAGULL SAFETY LTD
 45 CHESTNUT AVENUE,
 WOKINGHAM, BERKSHIRE,
 RG41 3HW, ENGLAND, UNITED KINGDOM
 TEL: 44-118-978 3978 FAX: 44-118-977 5261

REGIONAL OFFICE :
SEAGULL SAFETY (S) PTE LTD
 1 GENTING LINK,
 #07-06 PERFECT INDUSTRIAL BUILDING,
 SINGAPORE 349518
 TEL: 65-747 9646 FAX: 65-744 4028

THIS IS THE PROPERTY OF SEAGULL SAFETY LTD AND IS ONLY ISSUED ON CONDITION THAT NO COPY IS TAKEN OR REPRODUCTION OR DISCLOSURE TO A THIRD PARTY EITHER WHOLLY OR IN PART IS MADE WITHOUT THE WRITTEN CONSENT OF SEAGULL SAFETY LTD.

TITLE : FLAMEPROOF & WEATHERPROOF MOTOR DRIVEN SIREN FP6	
DRAWN BY : SA	DATE : 21.07.1993
CHECKED BY : -	DATE : -
DRWG NO : SS77100-02	REVISION 1