



**DESCRIPTION**

WEATHERPROOF MOTOR DRIVEN SIREN  
(SINGLE ROTOR)

**SPECIFICATION**

MOUNTING : HORIZONTAL MOUNT  
SOUND OUTPUT @ 1 METRE : 135db  
SOUND FREQUENCY : 475Hz  
VOLTAGE : 400VAC

**MODEL**

GP6

PHASE : 3  
MOTOR POWER : 2200 WATTS  
NORMAL RATING : CONTINUOUS  
START CURRENT : 3.5 Amps (400V)  
RUN CURRENT : 4.5 Amps (400V)  
WEIGHT : 68 kg  
INGRESS PROTECTION : IP 55  
FINISH : ENAMEL GREY, RED ROTOR

ALL DIMENSIONS IN MILLIMETERS

REV.	DATE	DESCRIPTION	DRAWN	CHECK D
0	19.07.93	ISSUED FOR APPROVAL	S.A.	
1	24.07.98	REVISED TRK	S.A.	



HEAD OFFICE :  
**SEAGULL SAFETY LTD**  
45 CHESTNUT AVENUE  
WOKINGHAM, BERKSHIRE  
RG44 3HW, ENGLAND UNITED KINGDOM  
Tel: 44-118-978 3978 Fax: 44-118-977 5261

REGIONAL OFFICE :  
**SEAGULL SAFETY (S) PTE LTD**  
1 GENTING LINK  
#07-06 PERFECT INDUSTRIAL BUILDING  
SINGAPORE 349578  
Tel: (65) 747 9646 Fax: (65) 744 4028

THIS IS THE PROPERTY OF SEAGULL SAFETY LTD AND IS ONLY ISSUED ON CONDITION THAT NO COPY IS TAKEN OR REPRODUCTION OR DISCLOSURE TO A THIRD PARTY EITHER WHOLLY OR IN PART IS MADE WITHOUT THE WRITTEN CONSENT OF SEAGULL SAFETY LTD.

TITLE :		<b>GP6 WEATHERPROOF MOTOR DRIVEN SIREN</b>	
DRAWN BY	SA	DATE	19.07.1993
CHECKED BY		DATE	
DRAWING NO :		<b>SS77100-05</b>	
REVISION		1	