




Digital Linear Heat Detection

- Seagull LHD (Linear Heat Detector) is a cable type sensor capable of detecting heat from a fire over its entire length
- Suitable for open area as well as proximity detection.
- Also ideal for confined areas or harsh environments which prohibit the use of other forms of detection
- Compatible with any fire control panel that is capable of accepting contact closure type initiating devices
- Simple and cost effective installation



SEAGULL LHD DIGITAL

Fixed Temperature Detector

SEAGULL LHD - DIGITAL

- FM approved with up to 20 feet between parallel runs.
- Two core cable.
- Fixed temperature detection - insulation designed to melt at a specific temperature enabling the two inner cores to short circuit
- Five different alarm temperature cables available.
- Monitoring equipment detects the short circuit and activates its alarm sequence.

Cable Construction



Conductor:

Tinned copper covered steel

Insulation:

Temperature Sensitive, Thermoplastic or Fluoropolymer

Outer Sheath:

PVC, Nylon or Fluoropolymer entire length.

Seagull LHD - Digital Cable Type	Material	Max. Ambient Storage Temp.	Min. Operating Temp.	Alarm Temperature	Flame Detection	Applications
Type S888-LHD105	Black PVC outer sheath	70°C	-30°C	105°C	12sec (max.)	Excluding areas contaminated by chemical agents
Type S888-LHD176	Red PVC outer sheath	105°C	-40°C	176°C	20sec (max.)	Excluding areas contaminated by chemical agents
Type S888-LHD240	White fluoropolymer outer sheath	200°C	-50°C	240°C	20sec (max.)	For high ambient temperatures or protection against chemical agents



S888-LHD/DIM Digital Interface Module



- Volt free relay outputs for Fire and Fault
- Provides monitoring of faults on both field wiring and the LHD
- LED Fire and Fault indicators
- Remote LED indicator outputs for both Fire and Fault
- Fire and Fault Test Functions
- Suitable for monitoring hazardous area applications when using safety barriers
- DIN Rail compatible

APPLICATION

The Digital Interface Module (DIM) monitors the Linear Heat Detection (LHD) cable for both Fire and Fault (open circuit) conditions. By the use of an additional series resistor it can also offer discrimination of a short circuit fault on the interposing field wiring.

With the ability to monitor up to 5000m for both Fire and Fault conditions the DIM enhances any fire detection capability and allows an appropriate action to be taken.

The DIM has volt free relay outputs for Fire and Fault which can be configured for connecting directly into a conventional fire alarm panel or addressable interface module.

As well as having Fire and Fault indicators built in, it has two pairs of outputs for driving remote LED indicators for Fire and Fault.

- Power Generation
- Cable Trays / Tunnels
- Road and Rail Tunnels
- Car Parks
- Conveyors (Bearing) protection
- Storage racks warehouse, Refrigerated rooms and cold stores.
- Petro-chemical storage tanks, rim seal protection
- Motor and pump overheat detection.
- Dirty and dusty environments.
- Building exteriors under eaves

TECHNICAL SPECIFICATION

ELECTRICAL

Operating voltage
21 - 30 VDC

Operating Current
Normal
25 mA (Fault relay energised)

Fire Alarm (max)
56 mA

OUTPUTS

Fire
2 x VFCO relays, 1.0 Amp 24VDC / 120 VAC

Fault
1 x VFCO relays, 1.0 Amp 24VDC / 120 VAC

Remote indicator outputs
4 x 100 mA

Inputs
Reset and lamp test

Maximum length of LHD
5,000m

MECHANICAL

Dimensions
H90 x W71 x D58 mm



ISO 9001:2015 CERT NO.: 621945

Seagull Safety Ltd
45 Chestnut Avenue,
Wokingham RG41 3HW
Berkshire, England
Tel: (44) 1753 474 112
Fax: (44) 118 977 5261

Seagull Safety (Singapore) Pte Ltd
1 Genting Link,
#07-06 Perfect One
Singapore 349518
Tel: (65) 6747 9646
Fax: (65) 6744 4028

Email: info@seagullssafety.com

www.seagullssafety.com



S888-LHD/DLI/2 Digital Location Interface (Monitoring distance 2Km)



- Detection & display of Alarm location for the complete length of LHD cable from 0m to 1,999m
- 3½ Digit LCD
- LED Fire and Fault indicators
- Fire and Fault Test Functions
- Suitable for monitoring hazardous area applications using safety barriers
- DIN Rail mounted or IP 65 Housing available
- Volt free relay outputs for Fire and Fault
- 4 - 20mA output
- Configurable for 2 wire mode
- Remote reset input

APPLICATION

The Digital Location Interface (DLI) monitors the Linear Heat Detection (LHD) cable and when activated identifies the location of the alarm. The distance in meters is then displayed on the 3½ digit LCD. Providing detection and location along the complete length of the LHD cable.

With the ability to monitor up to 2000m for both Fire and Fault conditions the DLI enhances any fire detection capability and allows an appropriate action to be taken.

The DLI offers flexible interfacing options, designed as a two wire device for connecting directly into a conventional fire alarm panel, it also has the ability to signal via volt free relay contacts for Fire and Fault, plus a 4-20 mA output representing 0m to 2000m.

The DLI is available as a DIN Rail mountable unit or fitted into an IP 65 weather proof enclosure.

- Power Generation
- Cable Trays / Tunnels
- Road and Rail Tunnels
- Car Parks
- Conveyors (Bearing) protection
- Storage racks warehouse, Refrigerated rooms and cold stores.
- Petro-chemical storage tanks, rim seal protection

TECHNICAL SPECIFICATION

ELECTRICAL

Operating voltage	14 - 30 VDC Two wire mode 20 - 30 VDC Relay mode
Operating Current	
Normal Quiescent	1.7 mA Two wire mode 11.5 mA Relay mode
Fire Alarm (max)	12 mA Two wire mode 29 mA Relay mode
Fault Condition	700 uA

OUTPUTS

Fire	2 x VFCO relays, 1 amp 24 VDC / 120 VAC Resistive
Fault	2 x VFCO relays, 1 amp 24 VDC / 120 VAC Resistive 4 - 20 mA signal loop output

LCD 3½ Digit (Accuracy ±1 digit, Tolerance ±3%)

Input Remote Reset

Maximum Length of LHD 2,000m

MECHANICAL

Dimensions	H105 x W86 x D58 mm (DIN Rail version) H200 x W164 x D116 mm (Polystyrene enclosure)
Cable Entries	4 x M20, 1 x M25 Top 4 x M20, 1 x M25 Bottom 2 x M20 each side.



ISO 9001:2015 CERT NO.: 621945

Seagull Safety Ltd
45 Chestnut Avenue,
Wokingham RG41 3HW
Berkshire, England
Tel: (44) 1753 474 112
Fax: (44) 118 977 5261

Seagull Safety (Singapore) Pte Ltd
1 Genting Link,
#07-06 Perfect One
Singapore 349518
Tel: (65) 6747 9646
Fax: (65) 6744 4028

Email: info@seagullssafety.com

www.seagullssafety.com



S888-LHD/DLI/10 Digital Location Interface (Monitoring distance 10Km)



- Detection & display of Alarm location for the complete length of LHD cable from 0m to 9,999m
- 4 Digit LCD
- LED Fire and Fault indicators
- Fire and Fault Test Functions
- Suitable for monitoring hazardous area applications using safety barriers
- DIN Rail mounted or IP 65 Housing available
- Volt free relay outputs for Fire and Fault
- 4 - 20mA output
- Configurable for 2 wire mode
- Remote reset input

APPLICATION

The Digital Location Interface (DLI) monitors the Linear Heat Detection (LHD) cable and when activated identifies the location of the alarm. The distance in meters is then displayed on the 4 digit LCD. Providing detection and location along the complete length of the LHD cable.

With the ability to monitor up to 10,000m for both Fire and Fault conditions the DLI enhances any fire detection capability and allows an appropriate action to be taken.

The DLI offers flexible interfacing options, designed as a two wire device for connecting directly into a conventional fire alarm panel, it also has the ability to signal via volt free relay contacts for Fire and Fault, plus a 4-20 mA output representing 0m to 10,000m.

The DLI is available as a DIN Rail mountable unit or fitted into an IP 65 weather proof enclosure.

- Power Generation
- Cable Trays / Tunnels
- Road and Rail Tunnels
- Car Parks
- Conveyors (Bearing) protection
- Storage racks warehouse, Refrigerated rooms and cold stores.

TECHNICAL SPECIFICATION

ELECTRICAL

Operating voltage 14 - 30 VDC Two wire mode
20 - 30 VDC Relay mode

Operating Current
Normal Quiescent 1.7 mA Two wire mode
11.5 mA Relay mode

Fire Alarm (max) 12 mA Two wire mode
29 mA Relay mode

Fault Condition 700 uA

OUTPUTS

Fire 2 x VFCO relays, 1 amp
24 VDC / 120 VAC Resistive

Fault 2 x VFCO relays, 1 amp
24 VDC / 120 VAC Resistive

4 - 20 mA signal loop output

LCD 4 Digit (Accuracy ±1 digit,
Tolerance ±3%)

Input Remote Reset

Maximum Length of LHD 10,000m

MECHANICAL

Dimensions H105 x W86 x D58 mm (DIN Rail version)
H200 x W164 x D116 mm (Polystyrene enclosure)

Cable Entries 4 x M20, 1 x M25 Top
4 x M20, 1 x M25 Bottom
2 x M20 each side.



ISO 9001:2015 CERT NO.: 621945

Seagull Safety Ltd
45 Chestnut Avenue,
Wokingham RG41 3HW
Berkshire, England
Tel: (44) 1753 474 112
Fax: (44) 118 977 5261

Seagull Safety (Singapore) Pte Ltd
1 Genting Link,
#07-06 Perfect One
Singapore 349518
Tel: (65) 6747 9646
Fax: (65) 6744 4028

Email: info@seagullssafety.com

www.seagullssafety.com