




Air Horns



- Air horns only need compressed air for operation
- Air horns can be used in hazardous areas
- Safe area air compressors can be provided

Air Horn		
Part No.	Frequency (Hz)	dB@1 Metre
S888-660/125	660	125
S888-387/125	387	125
S888-307/125	307	125
S888-370/132	370	132
S888-370/120	370	120
S888-315/134	315	134
S888-315/124	315	124
S888-200/145	200	145
Triple Unit		
S888-024/120	300/320/340	148





SEAGULL SAFETY

Air Horn & Compressor System



Air horn alarm systems are a low cost option for a very loud alarm, giving a penetrating tone of 350Hz coded as necessary.

There are many options that can be added, but the basic system has the air horn giving 143dB @ 1m, suitably located, with a back up air supply compressor and a manual initiation lever valve.

Normal systems can contain 1-3 air horns as required.


COMPRESSOR

- Suitably sized to give adequate capacity for alarm duration required.
- Automatic topping up of air pressure before and during alarm.




ALARM VALVE

- Lever valve allowing manual alarm initiation.
- This can also be used for testing air horns by opening a minimal amount as required.



SOLENOID VALVE

- Activation by electrical remote push button.



MOBILE PHONE INITIATION

- We can provide systems whereby a standard mobile phone can initiate an alarm from a dedicated mobile phone number.



ISO 9001:2015 CERT NO.: 621945

Seagull Safety Ltd
45 Chestnut Avenue,
Wokingham RG41 3HW
Berkshire, England
Tel: (44) 1753 474 112
Fax: (44) 118 977 5261

Seagull Safety (Singapore) Pte Ltd
1 Genting Link,
#07-06 Perfect One
Singapore 349518
Tel: (65) 6747 9646
Fax: (65) 6744 4028

Email: info@seagullssafety.com

www.seagullssafety.com